GAM839

Heavy Duty All-Position Tire • Better Damage Resistance & Long Service Life



All position

Overview

Rim Sizes:20-22.5

Aspect Ratio:mm

Section Width:210-305

Speed Rating:K-L

Features	Benefits
Reinforced belt construction	Protects casing from external punctures and delivers strong resistance against tread bursting
Strong casing with high tensile and thick cord structure	Strong casing strength for increase durability and reliability under continuous load stress
Giti Specially reinforced bead structure	Strong bead for better damage resistance in heavy load operating conditions
Special groove design in the center and V shape on the outer groove	Prevents and removes groove stone trapping,protecting the tire from road hazards
Unique shoulder groove design	Promotes heat dissipation and therefore cooler running, while preventing shoulder separation
Wear resistance and anti-cut and chip compound	Provides optimal wear life and resistant to damage from cuts
Optimized rib ratio and high pattern block rigidity	Effectively improves pattern rigidity and uniform force distribution on the tread, reducing occurrence of irregular wear

Giti - GAM839 offers 4 different tyre sizes

	Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load(kg)	kPa	PSI
TUBE TYPE	10.00R20	18PR	149/146	K	7.5	1054	16.2	3250/3000	930/930	135/135
	11.00R20	18PR	152/149	K	8	1085	16	3550/3250	930/930	135/135

TUBELESS	11R22.5	16PR	148/145	K	8.25	1054	16.2	3150/2900	850/850	123/123
	12R22.5	18PR	152/149	L	9	1085	16	3550/3250	930/930	135/135