

# GAO822

High Traction for Off-Road Usage • Durability & Extended Service Life



All position



## Overview

**Rim Sizes:**16-24

**Aspect Ratio:**0-95mm

**Section Width:**191-325

**Speed Rating:**J-J

Features	Benefits
Aggressive block pattern and open shoulder design	Provides high traction, with self-cleaning performance
Deep tread pattern design	Provide longer tire service life
Tie-bar design between center blocks	Effectively prevents pattern blocks from tearing
Reinforced casing and bead structure	Improves durability of casing and bead, and increasing tire damage resistance in heavy load operating conditions
Specially formulated tread compound	Provides strong cut and chip resistance on tough off road conditions
Thickened base rubber	Protects groove bottom from tearing and puncturing

## Giti - GAO822 offers 6 different tyre sizes

	Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load(kg)	kPa	PSI
TUBE TYPE	8.25R20	16PR	139/137	F	6.50	986	18.7	2430/2300	930/930	135/135
	11.00R20	18PR	152/149	F	8.00	1096	23.5	3550/3250	930/930	135/135
	12.00R20	20PR	156/153	F	8.50	1136	24.5	4000/3650	900/900	130/130
	12.00R24	20PR	160/156	F	8.50	1226	31	4500/4000	850/850	123/123
TUBELESS	295/80R22.5	18PR	152/149	J	9.00	1050	21	3550/3250	900/900	130/130

12R22.5	18PR	152/149	F	9.00	1096	23.5	3550/325	930/930	135/135
							0		

---