GAR558

Longer operating life • Irregular Wear Resistant • Excellent Durability & Damage Resistant



All position



Overview

Rim Sizes:20-22.5
Aspect Ratio:mm
Section Width:210-279
Speed Rating:K-M

Features	Benefits
Widened tread width design	Large tread volume area for extended wear life
Four belt construction	Effectively optimizes crown stiffness and tire contact
	surface pressure, promoting long wear life
Special wear-resistant compound	Promotes long wear life
Optimal rib ratio and rigidity of tread pattern	Equalizes distribution of tire contact surface pressure,
	preventing tire from irregular wear
Advanced Equal Force Casing technology	Uniform force distribution enables optimal tire footprint at
	various loads level thus result in regular tread wear
Big groove wall design and Anti-stone trapping groove	Effectively prevents stone trapping, protecting the tire
bottom	from road hazards
Shoulder void design and zigzag longitudinal groove	Provides effective heat dissipation and better resistance
	against damages

Giti - GAR558 offers 7 different tyre sizes

	Tire Size	PR	Load Index	Speed	Approved	Outer	Tread	Max	kPa	PSI
				Rating	Rim	Diameter	Depth	Load(kg)		
				,		(mm)	(mm)		,	-
TUBE TYPE	8.25R20	16PR	139/137	K	6.5	974	14	2430/230 0	930/930	135/135
	9.00R20	16PR	144/142	K	7	1019	14.5	2800/265	900/900	130/130

								0		
TUBELESS	10.00R20	18PR	149/146	К	7.5	1054	15	3250/300 0	930/930	135/135
	11.00R20	18PR	152/149	К	8	1085	15.3	3550/325 0	930/930	135/135
	9R22.5	14PR	136/134	М	6.75	974	14	2240/212 0	830/830	120/120
	10R22.5	16PR	144/142	М	7.50	1019	14.8	2800/265 0	900/900	130/130
	11R22.5	16PR	148/145	М	8.25	1054	15.8	3150/290 0	850/850	123/123