

GDM623

Excellent Traction and Grip • Durability & Long Service Life



Drive



Overview

Rim Sizes:16-24

Aspect Ratio:95mm

Section Width:178-325

Speed Rating:J-K

Features	Benefits
Intertwining tread pattern with deep grooves	Provides excellent traction and braking for safer driving
Sipe design in center pattern blocks	Strengthened wet grip performance
Thickened base rubber	Protects groove bottom from tearing and puncturing
Reinforced casing and bead structure	Improves durability of casing and bead,increasing tire damage resistance from heavy load operating conditions
Special anti cut and chip compound	Delivers excellent protection from tread cuts and damage in aggressive road and off-road conditions
Stone ejection design on the groove bottom	Prevents groove from stone trapping and penetration

Giti - GDM623 offers 3 different tyre sizes

	Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load(kg)	kPa	PSI
TUBE TYPE	7.00R16LT	14PR	118/114	K	5.50F	785	14.5	1320/1180	770/770	110/110
	7.50R16LT	14PR	122/118	K	6.00G	805	15	1500/1320	770/770	110/110
	8.25R16LT	16PR	128/124	K	6.50H	855	15	1800/1600	770/770	110/110