

# GSR225

Resist Irregular Wear • Longer Mileage • Better in Handling



Steer



## Overview

**Rim Sizes:**19.5-22.5

**Aspect Ratio:**0-80mm

**Section Width:**225-315

**Speed Rating:**J-M

Features	Benefits
Four belt construction	Increases casing and tread stiffness, minimizing tire deformation for longer wear
Advanced Equal Force Casing technology	Uniform force distribution enables optimal tire footprint at various loads level thus result in regular tread wear
Widened tread layout	Large tread volume for extended wear life
Giti specially-formulated tread compound	Improved wear resistance of tread
Resilient four vertical groove and zig-zag bottom design	Provides better handling and controllability of vehicle
Mutiple sipes along the side of groove	Self cleaning capability and higher resistance to damage from road hazards
Tire casing designed for retreadability	Higher retreadable capabilities
FEA bead construction optimization concept for bead construction	Optimizes and uniformly distributes load pressure to the bead, minimizing damage

## Giti - GSR225 offers 4 different tyre sizes

	Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load(kg)	kPa	PSI
TUBELESS	225/70R19.5	14PR	128/126	L	6.75	811	13	1800/1700	760/760	110/110
	245/70R19.5	18PR	141/140	M	7.50	839	14	2575/2500	860/860	125/125
	245/70R19.5	16PR	136/134	M	7.50	839	14	2240/2120	830/830	120/120

285/70R19.5 16PR

146/145

M

8.25

895

14.5

3000/290 900/900

130/130

0

---