

GT867

Longer Mileage • High Durability



All position



Overview

Rim Sizes:19.5-22.5

Aspect Ratio:0-80mm

Section Width:203-315

Speed Rating:J-M

Features	Benefits
Wear resistant compound for urban bus/haulage operation, in high frequency of start, stop and turning use	Excellent longer wear performance match to needed operation
Advanced Equal Force Casing technology	Uniform force distribution enables optimal tire footprint at various loads level thus result in regular tread wear
Zig-Zag groove and mutiple angle sipes	Provides excellent traction & prevents skidding on wet roads
Sidewall protector rib	Protects casing and sidewall from road hazard and curbing damage
Tire casing designed for retreadability	Higher retreadable capabilities

Giti - GT867 offers 4 different tyre sizes

Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load(kg)	kPa	PSI
TUBELESS 315/80R22.5	18PR	158/150	J	9.00	1076	18.7	4250/3350	900/900	131/131
305/70R22.5	16PR	152/150(154/150)	J(E)	9.00	1000	19	3550/3350	860/860	125/125
305/70R22.5	20PR	151/148	J	9	1006	19	3450/3150	900/900	130/130
12R22.5	18PR	152/149	J	9.00	1085	18.7	3550/3250	930/930	135/135